


Fall Protection Equipment

- Fall Protection Vest
- Fall Protection Overalls
- Full Body Harness
- Work Positioning Belts
- Work Positioning Lanyards
- Fall Arrest Lanyards
- Energy Absorbers
- Safety Hooks
- Rope Grabs
- Fall Arrest Blocks
- Confined Space Systems
- Horizontal lifeline Systems
- Vertical lifeline Systems
- Rescue Systems
- Anchor Systems

**FS 502 - Fall Arrest Lanyard
"Twin Lanyard"**



Large Hook double action

White threads

Karabiner double action
Screw-lock

Energy absorber

25mm Poliéster
webbing

Attachment Point:

- 2 Large Hooks
- 1 Karabiner

Description:

- Two large hook with double action lock and 60mm opening to connect into anchor point on structure, 1 karabiner with double action screw-lock and opening 20mm, connect to front chest attachment or dorsal attachment on full body harness, fall protection vest or fall protection overall.

- Webbing width 25mm double sewed colour orange, incorporated energy absorber which reduces force at fall to max. 6kN.

Material Software:

- Webbing polyester width 25mm, breaking strength >25000N
- Webbing polyester width 44mm, breaking strength >25000N
- Stitches with high strength polyester thread No. 10 - >180N
- Tear webbing action in accordance with EN 355 between 2KN and 6KN

Material Hardware:

- Karabiner in light alloy aluminium with 20mm opening double locking function and black anodized (EN362 certified)
- Large Hook in light alloy aluminium with 60mm opening double locking function and black anodized (EN362 certified)

Standard:

- EN355 and EN354 CE marked

Length:

- 2M

Weight:

- 1,7kg

Manufacturer:



Fallsafe-Online Lda - Zona Industrial da Varziela – Rua B Lote 54 – 4480-620 Vila do Conde, Portugal
Tel.: (+351)252 480 060 Fax.: (+351) 252 480 069
E-mail: support@fallsafe-online.com Website: www.fallsafe-online.com